

Coscat® 8330
Technical Data Sheet



Product Identification

Coscat® 8330 catalyst is a proprietary organo-metallic compound that was specifically developed to impart performance similar to that of the mercurial catalysts, without the toxicity issues associated with these excellent performing catalyst systems, for two component polyurethane systems.

Coscat® 8330 catalyst is recommended as a sole or co-catalyst in polyurethane elastomer systems typically requiring lead, mercury or tin catalysts. Specific benefits of Coscat® 8330 include a high selectivity toward the polyol-isocyanate reaction, thus avoiding bubble generation at low levels of moisture, excellent synergy with organo-mercurial catalysts and improved humid aging performance in urethane systems currently catalyzed with other organo-metallics or amines.

	Property	Value
Physical Properties	Active Ingredient	100%
	Appearance	Clear, liquid
	Color	2
	Density, lbs./gal, 25°C	9.63
	Metal Content	20
	Specific Gravity @ 25°C/25°C	1.158
	Viscosity, G-H @ 25°C	Z-10

- Applications**
- Slow to moderate speed catalyst for polyurethane coatings, elastomers and casting compounds
 - Does not foam in the presence of low levels of moisture
 - Toxic heavy metal free
 - Urethane Intermediates, Polymers
 - Chemical Intermediates

For toxicity or regulatory information please consult the Material Safety Data Sheet.

Information contained in this technical data sheet is believed to be accurate. Vertellus Performance Materials Inc. assumes no liability and makes no warranty or representation that the information is correct or complete and EXPRESSLY DISCLAIMS ALL REPRESENTATIONS OR WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Final determination of suitability of any material and issues of patent infringement is the sole responsibility of the user who alone knows the conditions of intended use. Our customers should ensure that any product incorporating a Vertellus ingredient is safe for its intended use pursuant to applicable law and that any necessary disclosures to consumers have been made.

Vertellus Performance Materials Inc., 2110 High Point Road, Greensboro, NC 27403 USA
USA Tel: 800-227-2436 **USA Fax:** 336-854-4058 **USA Email:** VPM-TechServices@vertellus.com
Web: www.vertellus.com