

Lubricin® N-1
Technical Data Sheet



Product Identification

A highly refined methyl ricinoleate for lubricating oils, motor fuels, upper cylinder lubricants, cutting oils and gear oils. It functions to reduce rusting, corrosion and wear of metal parts and exhibits detergent action on tar, varnish and carbon deposits.

	<u>Property</u>	<u>Value</u>
Physical Properties	Acid Value	0.7
	Boiling Point @ 1mm, °C	170
	Color, Gardner	3
	Composition	Methyl Ricinoleate
	Density, lbs./gal, 25°C	7.70
	Fire Point, COC, °F	420
	Flash Point, COC, °F	370
	Form	Clear liquid
	Hydroxyl Value	170
	Iodine Value	85
	Molecular Weight	310
	Pour Point, °F	-20
	Refractive Index	1.4620
	Saponification Value	178
	Specific Gravity, 25°C/25°C	0.925
Viscosity, 25°C, Stokes	0.3	
Viscosity, SUS @ 100°F	97 Seconds	
Viscosity, SUS @ 210°F	37 Seconds	

Applications

- Upper cylinder lubricant as a highly effective detergent for the removal of carbon.
- As an oiliness agent in transmission oil and in the lubricant-gas mixture for two-cycle engines.
- Added to methanol in combination with nitro-methane in model plane fuels to minimize gum formation.
- In standard cutting oils to improve oiliness and adhesion to hot metal and to produce a brighter finish on the metal being worked.

For toxicity or regulatory information please consult the Material Safety Data Sheet.

Information contained in this technical data sheet is believed to be accurate. Vertellus Performance Materials Inc. assumes no liability and makes no warranty or representation that the information is correct or complete and EXPRESSLY DISCLAIMS ALL REPRESENTATIONS OR WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Final determination of suitability of any material and issues of patent infringement is the sole responsibility of the user who alone knows the conditions of intended use. Our customers should ensure that any product incorporating a Vertellus ingredient is safe for its intended use pursuant to applicable law and that any necessary disclosures to consumers have been made.

Vertellus Performance Materials Inc., 2110 High Point Road, Greensboro, NC 27403 USA
 USA Tel: 800-227-2436 USA Fax: 336-854-4058 USA Email: VPM-TechServices@vertellus.com
 Web: www.vertellus.com